



|          | A       | B       | Ribs | Arms |
|----------|---------|---------|------|------|
| ML-FAA-4 | 100"    | 87"     | 24   | 5    |
| ML-FAA-3 | 75 3/4" | 62 3/4" | 18   | 4    |
| ML-FAA-2 | 51 1/2" | 38 1/2" | 12   | 3    |
| ML-FA-4  | 89 1/2" | 76 1/2" | 24   | 2    |
| ML-FA-3  | 69"     | 56"     | 18   | 2    |
| ML-FA-2  | 48"     | 35"     | 12   | 2    |
| ML-FA-1  | 27 1/2" | 14 1/2" | 6    | 2    |
| ML-F-4   | 82 1/2" | 69 1/2" | 24   | 0    |
| ML-F-3   | 62"     | 49"     | 18   | 0    |
| ML-F-2   | 41 1/2" | 28 1/2" | 12   | 0    |
| ML-F-1   | 20 3/4" | 7 3/4"  | 6    | 0    |

### Overview

Patented, intensive use bench style seating system, available in varying lengths and configurations. Intended for indoor or outdoor use. Engineered for institutional durability. Available with or without arms. Free standing or bolt-down. Modular design.

### Fabrication:

Two component system consisting of ribs and frame.

**Ribs:** 3" wide, centered on 3 1/2" collar. Six ribs equals a standard 21" seat.

**Frame:** Legs are formed and welded to two crossbar tubes with end caps. Welds ground smooth and polished before powder coating.

### Material:

**Ribs:** Injection molded, high impact polypropylene with ultra violet light stabilizers (to reduce fading) or fire retardant additives. Chemically resistant to acetone, blood, vinegar, urine, feces, salt solution, and chlorine solution.

**Frame:** Powder coated steel, 2 1/2" x 3/8" bar stock, sled base legs with predrilled 1/2" anchor holes, with 2" diameter, 14 gauge cross support tubes.

**Paint:** Frames for outdoor use are zinc coated prior to powder painting for enhanced rust protection.

### Performance Test Standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies (Indoor version only).

### Color:

**Rib Colors:** Fog Grey, Teal, Plum, Slate Blue.

**Frame Colors:** Fog Grey.

### Weight:

Varies with size. Contact manufacturer.

### Assembly:

No assembly required.

### Installation:

Fasten frame to floor. May be used free standing. Floor mounting hardware not included.

### Warranty:

5 year limited replacement warranty.

### Maintenance:

Easily cleaned with a damp cloth and a mild soap solution.

### Filing System:

12600 Institutional Furniture

11197 Correctional Furniture