

Econo-Max[®] Table - Stainless Steel Quietcore Top



Dimensions

SSS Seat Height 19.75"

SST Seat Height 19.25"

Overall Height 31.75"

Model/Weight

See Additional Dimensions



Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 10/16

Fabrication & Material

Base: The curved member that supports the top has a 10" radius bend to facilitate easy cleaning beneath the table. This curved piece is fully welded to a vertical steel tube that supports the seat. The top of the curved tubes and top of the seat tubes have fully welded 6" x 6" x 1/4" thick steel plates for mounting top and seats. Bottom of seat tube has a fully welded mounting plate inset. For free standing applications, the inset is threaded to accommodate a tamper and skid resistant, adjustable glide with a 1/2" diameter stem. For bolt-down application, the inset has a hole for the fully enclosed tamper-resistant bolt-down system. 2 1/2" diameter, 14 gauge steel tubing.

Top: Durable 18 gauge stainless steel top surface wrapped around sound deadening particle board core with embedded T-nuts. 1 1/4" edge profile.

Super Slammer Stone[®] Seats: 13" diameter high density color impregnated compression molded composite that is highly scratch and stain resistant. Four molded-in threaded inserts for superior metal-to-metal connection.

Stainless Steel Seats: 12" diameter one piece formed of 14 gauge steel with a 1 1/2" drop edge. Stainless steel mounting studs.

Made in the U.S.A.

Performance Test Standards

- Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Base: Grey.

Stainless steel: #4 finish

SlammerStone Seat: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Sea Spray, Raven

Options

Legs: Clear PVC leg protectors. Glides

Game tops (GT): Checkerboard available on Stainless Steel tops.

Assembly

Secure legs to top. Attach seats.

Installation

Fasten to floor. No installation required on free standing models. Concealed concrete expansion anchors included with bolt to floor option.

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Seats: Clean, Restore and Protect with Norix's 1-2-3 Care System for Molded Furniture.

Additional Dimensions

EMX4200-4 (42" Diameter) 174 lbs EMX5400-6 (54" Diameter) 230 lbs

Econo-Max[®] Table - Rectangle Stainless Steel Top



Dimensions

SSS Seat Height 19.75"

SST Seat Height 19.25"

Overall Height 31.5"

Model/Weight

See Additional Dimensions



Fabrication & Material

Base: The curved member that supports the top has a 10" radius bend to facilitate easy cleaning beneath the table. This curved piece is fully welded to a vertical steel tube that supports the seat. The top of the curved tubes and top of the seat tubes have fully welded 6" x 6" x 1/4" thick steel plates for mounting top and seats. Bottom of seat tube has a fully welded mounting plate inset. For free standing applications, the inset is threaded to accommodate a tamper and skid resistant, adjustable glide with a 1/2" diameter stem. For bolt-down application, the inset has a hole for the fully enclosed tamper-resistant bolt-down system. 2 1/2" diameter, 14 gauge steel tubing.

Top: Rectangle stainless steel, 12 gauge with a 1 1/2" drop edge and reinforcing channels. Four threaded inserts for each leg. Steel - baked on factory applied epoxy powder coated finish. Stainless Steel - type 304.

Super Slammer Stone[®] Seats: 13" diameter high density color impregnated compression molded composite that is highly scratch and stain resistant. Four molded-in threaded inserts for superior metal-to-metal connection.

Stainless Steel Seats: 12" diameter one piece formed of 14 gauge steel with a 1 1/2" drop edge. Stainless steel mounting studs.

Made in the U.S.A.

Performance Test Standards

- Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Base: Grey.

Stainless steel: #4 finish

SlammerStone Seat: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Sea Spray, Raven

Options

Game tops (GT): Checkerboard available on Stainless Steel tops.

Assembly

Secure legs to top. Attach seats.

Installation

Fasten to floor. No installation required on free standing models. Concealed concrete expansion anchors included with bolt to floor option.

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Seats: Clean, Restore and Protect with Norix's 1-2-3 Care System for Molded Furniture.

Additional Dimensions

EMX7233-6	(30" x 72")	250 lbs	EMX9633-8	(30" x 96")	322 lbs
-----------	-------------	---------	-----------	-------------	---------

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 10/16

Econo-Max[®] Table - Round Stainless Steel Top



Dimensions

SSS Seat Height 19.75"

SST Seat Height 19.25"

Overall Height 30.5"

Model/Weight

See Additional Dimensions



Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 10/16

Fabrication & Material

Base: The curved member that supports the top has a 10" radius bend to facilitate easy cleaning beneath the table. This curved piece is fully welded to a vertical steel tube that supports the seat. The top of the curved tubes and top of the seat tubes have fully welded 6" x 6" x 1/4" thick steel plates for mounting top and seats. Bottom of seat tube has a fully welded mounting plate inset. For free standing applications, the inset is threaded to accommodate a tamper and skid resistant, adjustable glide with a 1/2" diameter stem. For bolt-down application, the inset has a hole for the fully enclosed tamper-resistant bolt-down system. 2 1/2" diameter, 14 gauge steel tubing.

Top: Round stainless steel, 10 gauge, type 304 stainless steel with a 1 1/2" drop edge. Four stainless steel studs welded to the underside for attaching each leg.

Super Slammer Stone[®] Seats: 13" diameter high density color impregnated compression molded composite that is highly scratch and stain resistant. Four molded-in threaded inserts for superior metal-to-metal connection.

Stainless Steel Seats: 12" diameter one piece formed of 14 gauge steel with a 1 1/2" drop edge. Stainless steel mounting studs.

Made in the U.S.A.

Performance Test Standards

- Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Base: Grey.

Stainless steel: #4 finish

SlammerStone Seat: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Sea Spray, Raven

Options

Game tops (GT): Checkerboard available on Stainless Steel tops.

ADA compliant seat configuration available

Assembly

Secure legs to top. Attach seats.

Installation

Fasten to floor. No installation required on free standing models. Concealed concrete expansion anchors included with bolt to floor option.

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Seats: Clean, Restore and Protect with Norix's 1-2-3 Care System for Molded Furniture.

Additional Dimensions

EMX4204-4	(42" Diameter)	136 lbs	EMX5404-6	(54" Diameter)	234 lbs
EMX4205-4	(42" Diameter)	140 lbs	EMX5405-6	(54" Diameter)	240 lbs