

Forté™ Café Table - Laminate Top



Dimensions

Height 30.5"

Model/Weight

See Additional Dimensions



Fabrication & Material

Base: One-piece rotationally molded polyethylene with lightly textured maintenance free surface which allows for easy cleaning. Specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance.

Laminate Top: Selected laminate material bonded to a core of 45 lb density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1½" thick edge profile.

Made in the U.S.A.

Flammability Test Standards

Molded Base is compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Performance Test Standards

- Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Base: Moss, Fossil, Skiff

Laminate Top: Wilsonart® Montana Walnut 7110-60, Asian Sun 7951-38, Tan Echo 7941-38, Asian Sand 7952-38 with color coordinated molded edges.

Assembly

Refer to manufacturers instructions for assembly.

Installation

Ballast weighting required to validate warranty. Recommended 150 pounds of sand ballast, 200 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty. Intended as an indoor product.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Laminate Tops: Norix Cleaning Solutions' Wood Cleaner and Polish.

Additional Dimensions

FT610	(42" Diameter)	89 lbs	FT630	(48" Diameter)	112 lbs
FT620	(42" x 42")	92.5 lbs			

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 10/16

Forté™ Café Table - Molded Top



Model	FT600
Dimensions	
Height	29"
Diameter	36"
Weight	31 lbs



Fabrication & Material

One-piece rotationally molded polyethylene with lightly textured maintenance free surface which allows for easy cleaning. Specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance.

Made in the U.S.A.

Flammability Test Standards

Molded Base is compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Performance Test Standards

- Product tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Moss, Fossil, Skiff

Assembly

Refer to manufacturers instructions for assembly.

Installation

Ballast weighting required to validate warranty. Recommended 150 pounds of sand ballast, 200 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty. Intended as an indoor product.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Laminate Tops: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 5/16