

Titan® Bunkable Frame Style Bed (Steel Deck)



Model	TNT1611
Dimensions	
Length	81.25"
Width	38.5"
Height	37"
Weight	124 lbs



Fabrication & Material

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Connector Brackets: 3/8" thick.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 1,000 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Headboard & footboard (Wild Cherry - Standard, Optional Laminates: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush) Ladder. Safety rail. Floor anchor kit. Bunk lock clamps.

Glide kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal. Optional Decorative Laminate: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance.

For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 12/16

Titan® Bunkable Frame Style Bed (Steel Deck)



Model	TNT1611
Dimensions	
Length	86.25"
Width	38.5"
Height	37"
Weight	133 lbs



Fabrication & Material

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Connector Brackets: 3/8" thick.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 1,000 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Headboard & footboard (Wild Cherry - Standard, Optional Laminates: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush) Ladder. Safety rail. Floor anchor kit. Bunk lock clamps.

Glide kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal. Optional Decorative Laminate: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance.

For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 12/16

Titan® Bunkable Frame Style Bed (Steel Deck)



Model	TNT1611
Dimensions	
Length	86.25"
Width	56.5"
Height	37"
Weight	188 lbs



Fabrication & Material

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Connector Brackets: 3/8" thick.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 1,000 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Headboard & footboard (Wild Cherry - Standard, Optional Laminates: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush) Ladder. Safety rail. Floor anchor kit. Bunk lock clamps.

Glide kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal. Optional Decorative Laminate: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance.

For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 12/16

Titan® Frame Style Bunk Bed (Steel Deck)



Model	TNT1651
Dimensions	
Length	81.25"
Width	38.5"
Height	72"
Weight	248 lbs



Fabrication & Material

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Connector Brackets: 3/8" thick.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Laminate: Wild Cherry

Optional Laminate Colors: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush

Options

Headboard & footboard (Wild Cherry - Standard, Optional Laminates: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush) Ladder, Safety rail, Floor anchor kit, Glide kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal. Optional Decorative Laminate: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 12/16

Titan® Frame Style Bunk Bed (Steel Deck)



Model	TNT1651
Dimensions	
Length	86.25"
Width	38.5"
Height	72"
Weight	266 lbs



Fabrication & Material

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Connector Brackets: 3/8" thick.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Laminate: Wild Cherry

Optional Laminate Colors: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush

Options

Headboard & footboard (Wild Cherry - Standard, Optional Laminates: Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush) Ladder, Safety rail, Floor anchor kit, Glide kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model.

Warranty

10 year limited replacement warranty.

Maintenance

Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal. Optional Decorative Laminate: For wood products, Norix recommends using a mild wood cleaner for routine and regular cleaning maintenance. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of a regular-strength wood cleaner.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 12/16