

Titan® Lift Deck Bed



Model	TNT1646
Dimensions	
Width	82"
Depth	38"
Height	13.25"
Weight	225 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

Body: 18 gauge.

Bottom: 18 gauge.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Floor anchor kit.

Assembly

None required

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 5/16

Titan® Bunkable Lift Deck Bed



Model	TNT1616
Dimensions	
Width	86"
Depth	38.5"
Height	36"
Weight	253 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

Body: 18 gauge.

Bottom: 18 gauge.

End frame legs: 16 gauge.

End frame cross-members: 16 gauge.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Floor anchor kit. Bunk lock clamps. Glide Kit.

Assembly

Attach end frames to bed base with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Optional accessories attach to bed (with hardware supplied through purchase of accessories).

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 5/16