

Titan® Loft Bed (Spring Deck)



Model	TNT1850
Dimensions	
Length	80.625"
Width	38.5"
Height	73"
Weight	126-186 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 2" x 1.5" x 5/32" rail angle steel, sinuous 9 gauge wire connected by 13 gauge links with 12 gauge 16 turn helical springs. 8 gauge spring deck connector brackets.

End frame legs: 16 gauge

End frame cross members: 16 gauge

Desk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge band.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color (Spring Deck): Matte Ebony

Steel Color (End Frames): Khaki, Ebony

Optional Steel Colors (End Frames Only): Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Desk Model TNT1853. Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Safety Rail. Ladder. Glide kit

Assembly

Attach wedge lock brackets to end frames with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Secure spring deck bolts to wedge lock slots. Attach fascia/safety rail and headboard to end frames with furnished fasteners. Attach full-length Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 5/16

Titan® Loft Bed (Spring Deck)



Model	TNT1850
Dimensions	
Length	85.625"
Width	38.5"
Height	73"
Weight	126-186 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 2" x 1.5" x 5/32" rail angle steel, sinuous 9 gauge wire connected by 13 gauge links with 12 gauge 16 turn helical springs. 8 gauge spring deck connector brackets.

End frame legs: 16 gauge

End frame cross members: 16 gauge

Desk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge band.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 800 lb static load
- Certified to pass GSA 3FNE-99-582D Safety and Performance Test Requirement for Bunkable and Loftable Beds.

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color (Spring Deck): Matte Ebony

Steel Color (End Frames): Khaki, Ebony

Optional Steel Colors (End Frames Only): Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Desk Model TNT1853. Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Safety Rail. Ladder. Glide kit

Assembly

Attach wedge lock brackets to end frames with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Secure spring deck bolts to wedge lock slots. Attach fascia/safety rail and headboard to end frames with furnished fasteners. Attach full-length Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 5/16

Titan® Loft Bed (Steel Deck)



Model	TNT1750
Dimensions	
Length	80.625"
Width	38.5"
Height	73"
Weight	167-227 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge

End frame cross members: 16 gauge

Desk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge band.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Desk Model TNT1753. Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Safety Rail. Ladder. Glide kit

Assembly

Attach end frames to bed deck with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Optional accessories attach to bed (with hardware supplied through purchase of accessories). Attach fulllength Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 5/16

Titan® Loft Bed (Steel Deck)



Model	TNT1750
Dimensions	
Length	85.625"
Width	38.5"
Height	73"
Weight	167-227 lbs

**Fabrication & Material**

Cut, formed, welded steel, Powder coated steel.

Bed deck: 12 gauge.

End frame legs: 16 gauge

End frame cross members: 16 gauge

Desk Top/Fascia: High-pressure laminate over 3/4" 7-ply plywood substrate with 3mm PVC edge band.

Optional Headboard: 45 lb density M3 grade particle board with durable high-pressure laminate surface and 2mm PVC edge

Made in the U.S.A.

Performance Test Standards

- Tested to 1,000 lb static load

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Steel Color: Khaki, Ebony

Optional Steel Colors: Cream, London Fog, Pewter, Shark, Slate, Irish Moss, Dusk, Mink

Options

Desk Model TNT1753. Headboard & footboard (Wild Cherry - Standard. Optional Laminates - Kensington Maple, Solar Oak, Rustic Slate, Pewter Brush). Safety Rail. Ladder. Glide kit

Assembly

Attach end frames to bed deck with furnished hex socket button head fasteners (threaded inserts in vertical members of end frame). Select desired height for bed deck prior to assembly. Optional accessories attach to bed (with hardware supplied through purchase of accessories). Attach fulllength Desk Top to end frames in conjunction with connection of Stabilizer Bar, Support Bar and Bunk Connectors. Refer to manufacturers assembly instructions.

Installation

None required for standard model

Warranty

10 year limited replacement warranty.

Maintenance

Recommend using Norix Cleaning Solutions, specifically formulated for extended care of Norix products. Norix Cleaning Solutions' Stainless Steel Cleaner. Optional Decorative Laminate: Norix Cleaning Solutions' Wood Cleaner and Polish.

Norix Group, Inc.
 1800 W. Hawthorne Lane,
 Suite N
 West Chicago, Illinois 60185
 Phone: 630-231-1331
 Toll Free: 800-234-4900
 Fax: 630-231-4343
 Email: furniture@norix.com
 www.norix.com
 ©2016 Norix Group, Inc.

Specifications subject to
 change without notice.
 ©2016 Norix Group, Inc.
 All Rights Reserved.
 Printed in U.S.A. 5/16