

# Wink™ Lounge Arm Chair



<b>Model</b>	WC10
<b>Dimensions</b>	
Seat Height	18.5"
Seat Width	22"
Overall Height	31"
Depth	29"
Width	26"
Arm Height	25.25"
<b>Weight</b>	42 lbs



**Stinson**  
SEE / SAMPLE / SPEC

Norix Group, Inc.  
1800 W. Hawthorne Lane,  
Suite N  
West Chicago, Illinois 60185  
Phone: 630-231-1331  
Toll Free: 800-234-4900  
Fax: 630-231-4343  
Email: furniture@norix.com  
www.norix.com  
©2016 Norix Group, Inc.

Specifications subject to  
change without notice.  
©2016 Norix Group, Inc.  
All Rights Reserved.  
Printed in U.S.A. 12/16

## Fabrication & Material

**Frame:** One-piece rotationally molded polyethylene with lightly textured surface allows for easy cleaning. Specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading) is chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance. Molded-in access port with threaded screw cap for ballast weighting capability. Non-removable steel encased nylon glides for floor protection.

**Back:** 5" polyurethane foam is fully upholstered and stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection.

**Seat:** Upholstered 4" polyurethane foam with a 6" bullnose stapled to high strength plywood. Plywood is connected to the frame with tamper-resistant hardware and embedded steel T-nuts for a secure steel-to-steel connection. The seat features both a side and back cleanout for easy cleaning.

Made in the U.S.A.

## Flammability Test Standards

Optional upgrade for compliance with the following standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items

## Performance Test Standards

- Tested to 750 lb static load
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012

## Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Color

**Naturals Color Palette:** Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

**High Brights Color Palette:** Lime, Reef, Mango, Orchid

## Options

Ganging kit, Bolt down kit, Ballast: Dry pea gravel 50 lbs recommended, 75 lbs maximum. Replacement cushions are available and easily installed in the field. Seat and backs are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

## Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

## Assembly

None required

## Installation

Required for ganging plates and ballast. Recommended 50 pounds of sand ballast, 50 lbs maximum. Ballast not supplied by Norix.

## Warranty

10 year limited replacement warranty

## Maintenance

**Seats:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution. **Upholstery:** Refer to Upholstery Manufacturers' cleaning instructions.