

# Ultra-Max® Armless Chair



<b>Model</b>	C160
<b>Dimensions</b>	
Seat Height	144.5 cm
Seat Width	48 cm
Overall Height	80 cm
Depth	58.5 cm
Width	48 cm
<b>Weight</b>	7.7 kg



## Fabrication & Material

One-piece, rotationally molded, specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance. Full perimeter floor support to facilitate ease of cleaning and to prevent concealment of contraband. Molded-in steel threaded inserts for optional ganging side-to-side or bolt-down applications. Made in the U.S.A.

*Ligature-resistant design with no internal openings.*

## Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- UL94 HB Test for Flammability of Plastic Materials
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

## Performance Test Standards:

- ANSI/BIFMA X5.1 2002 General Purpose Office Chairs.
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (500 lbs from 18")

## Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

## Options

Polyethylene ganging plates, polyethylene ballasting bags (requires clean, dry sand provided by end user or installer), stainless steel plates for bolt-down application.

## Assembly

None required

## Installation

Required for bolt-down plates, ganging plates and ballast. Recommended 50 pounds of sand ballast, 100 lbs maximum. Ballast not supplied by Norix.

## Warranty

10 year limited replacement warranty.

## Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

Norix Group, Inc.  
1800 W. Hawthorne Lane,  
Suite N  
West Chicago, Illinois 60185  
Phone: 630-231-1331  
Toll Free: 800-234-4900  
Fax: 630-231-4343  
furniture@norix.com  
norix.com  
©2019 Norix Group, Inc.

Specifications subject to  
change without notice.  
©2019 Norix Group, Inc.  
All Rights Reserved.  
Printed in U.S.A. 1/19