

Mega-Max[®] Sectional Lounge Chair



Model	C170
Dimensions	
Seat Height	16.5"
Seat Width	30.5"
Overall Height	31.5"
Depth	29.5"
Width	30.5"
Weight	36 lbs



Fabrication & Material

One-piece, rotationally molded, specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance. Full perimeter floor support to facilitate ease of cleaning and to prevent concealment of contraband. Molded-in steel threaded inserts for optional ganging side-to-side, back-to-back or bolt-down applications. Made in the U.S.A.

Ligature-resistant design with no internal openings.

Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- UL94 HB Test for Flammability of Plastic Materials
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Performance Test Standards:

- ANSI/BIFMA X5.1 2002 General Purpose Office Chairs.
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (500 lbs from 18")

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

Options

Polyethylene ganging plates, polyethylene ballasting bags (requires clean, dry sand provided by end user or installer), stainless steel plates for bolt-down application.

Assembly

None required

Installation

Required for bolt-down plates, ganging plates and ballast. Recommended 50 pounds of sand ballast, 100 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green[®] or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox[®] Clean-Up[®] Cleaner + Bleach or an equivalent cleaning solution.

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
furniture@norix.com
norix.com
©2019 Norix Group, Inc.

Specifications subject to
change without notice.
©2019 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 1/19