

Forté® Café Table - Laminate Top



SPECIFICATIONS



Model	Dimensions	Weight
CA4200	(42" Diameter x 30.5"H)	89 lbs
CA4800	(48" Diameter x 30.5"H)	112 lbs
CA4242	(42"L x 42"W x 30.5"H)	92.5 lbs

*Intended for indoor use only



DETAILS

Color

Base: Moss, Fossil, Raven

Laminate Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve and Titanium Evolve Game Top with Black edge.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Factory installed ballasting available

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: One-piece, rotationally-molded polyethylene with lightly textured, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

Laminate Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel-to-steel connection for maximum long term reliability. Robust 1.5" thick edge profile. Made in the U.S.A.

Installation

Ballasting required to validate warranty. Recommended 100 pounds of sand or gravel ballast, 150 lbs maximum.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Performance Test Standards

Product tested to 1,000 lb static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospital's guidelines