

SPECIFICATIONS



Model

PRS-1721

Weight

1.5 lbs

*Intended for indoor use only

Dimensions

Width 21"

Length 17.5"

Height 5"

Note: Dimensional tolerances are +/- one inch.



DETAILS

Color

Silver

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Assembly

Shipped assembled in poly bag

Fabrication & Material

Sealed Seam Pillow

Polyester batting fiber is encased in a reinforced ripstop, fire-retardant, polyurethane coated cover with radio frequency welded seams for enhanced hygiene, security and durability. Premium cover is highly-puncture resistant and inhibits tearing if puncture does occur. Pillow is fluid, crack, peel, abrasion and bed bug resistant, anti-microbial and anti-fungal. Provides a virus barrier and is resistant to tearing and delaminating for greater infection control. Features two breathable vents that repel oil, water, blood, urine and other fluids. Batting is made of non-hazardous materials. Made in the U.S.A.

Warranty

5 year limited prorated warranty against seam failure and cover material cracking (Full warranty details available upon request).

Maintenance

- Use hospital-grade cleaner or bleach/water solution on the entire pillow.
- Completely rinse with clean water (do not submerge).
- After cleaning, dry the pillow cover thoroughly. Do not place wet pillow onto a sleep surface; moisture may cause cover fabric damage (not covered by Limited Warranty).
- Contact Norix Customer Service for a pillow patch kit to address minor punctures and tears.

TESTING

Performance Test Standards

- Tested to ASTM F1566 Hexagonal Roller Mattress Durability Test
- Tested to ASTM D751 Hydrostatic Resistance Test for Coated Fabrics

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

Compliant with the following flammability standards:

- 16 CFR Part 1633
- 16 CFR Part 1632
- California Technical Bulletin 129