

Forté™ Guest Armless Chair



Model	FC610
Dimensions	
Seat Height	46 cm
Seat Width	53 cm
Overall Height	83.5 cm
Depth	66.5 cm
Width	53 cm
Weight	10 kg



Stinson
SEE / SAMPLE / SPEC

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 12/16

Fabrication & Material

One-piece rotationally molded polyethylene with lightly textured maintenance free surface which allows for easy cleaning. Tamper-resistant steel encased nylon glides for floor protection. Molded-in steel threaded inserts for optional ganging side-to-side and molded in access port with threaded screw cap for sand ballast weighting capability. Rotationally molded, specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance. Made in the U.S.A.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Performance Test Standards

- Tested to 340 kg static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (227 kg from 46 cm)

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Plastic is Recyclable #7

Color

Naturals Color Palette: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

High Brights Color Palette: Lime, Reef, Mango, Orchid

Options

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Molded plywood shell is clearcoat finished to protect against fluid absorption. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133.

Ganging Kit, Bolt-Down Kit

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Installation

Required for ganging plates and ballast. Recommended 50 pounds of sand ballast, 100 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty

Maintenance

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution. Optional Upholstery: Refer to Upholstery Manufacturers' cleaning instructions.

Forté™ Guest Arm Chair



Model	FC600
Dimensions	
Seat Height	46 cm
Seat Width	47 cm
Overall Height	83.5 cm
Depth	66.5 cm
Width	61 cm
Arm Height	66.5 cm
Weight	12.7 kg



Stinson
SEE / SAMPLE / SPEC

Norix Group, Inc.
1800 W. Hawthorne Lane,
Suite N
West Chicago, Illinois 60185
Phone: 630-231-1331
Toll Free: 800-234-4900
Fax: 630-231-4343
Email: furniture@norix.com
www.norix.com
©2016 Norix Group, Inc.

Specifications subject to
change without notice.
©2016 Norix Group, Inc.
All Rights Reserved.
Printed in U.S.A. 12/16

Fabrication & Material

One-piece rotationally molded polyethylene with lightly textured maintenance free surface which allows for easy cleaning. Tamper-resistant steel encased nylon glides for floor protection. Molded-in steel threaded inserts for optional ganging side-to-side and molded in access port with threaded screw cap for sand ballast weighting capability. Rotationally molded, specially formulated, fire-retardant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color, fire retardancy and quality assurance. Made in the U.S.A.

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Performance Test Standards

- Tested to 340 kg static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (227 kg from 46 cm)

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Plastic is Recyclable #7

Color

Naturals Color Palette: Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

High Brights Color Palette: Lime, Reef, Mango, Orchid

Options

Optional upholstered plywood shell comes factory installed and can be easily removed for cleaning or replacement. Molded plywood shell is clearcoat finished to protect against fluid absorption. Cushioned comfort provided by polyurethane foam on back and seat. Upholstered flammability standard upgradeable to TB133.

Ganging Kit, Bolt-Down Kit

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Installation

Required for ganging plates and ballast. Recommended 50 pounds of sand ballast, 100 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty

Maintenance

Seats: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution. Optional Upholstery: Refer to Upholstery Manufacturers' cleaning instructions.