

# Harmony™ High Back Arm Chair



<b>Model</b>	LA-4X
<b>Dimensions</b>	
Seat Height	18"
Seat Width	23.5"
Overall Height	47.75"
Depth	33.25"
Width	32.5"
Arm Height	25.625"
<b>Weight</b>	138 lbs



**Stinson**  
SEE / SAMPLE / SPEC

Norix Group, Inc.  
1800 W. Hawthorne Lane,  
Suite N  
West Chicago, Illinois 60185  
Phone: 630-231-1331  
Toll Free: 800-234-4900  
Fax: 630-231-4343  
Email: furniture@norix.com  
www.norix.com  
©2016 Norix Group, Inc.

Specifications subject to  
change without notice.  
©2016 Norix Group, Inc.  
All Rights Reserved.  
Printed in U.S.A. 12/16

## Fabrication & Material

**Frame:** The Harmony Series is built around a robust fully welded steel frame for maximum strength and durability.

**Cushions:** Polyurethane foam is glued to high strength plywood and connected to a tamperproof steel seat pan which is welded directly to the frame. 2.7 pound high density polyurethane foam in both the seat and back provides longevity and support in high traffic applications. Upholstery is available in a wide selection of fabrics while steel plates conceal staples and tamper resistant fasteners provide reinforced security.

**Arm Panels:** Steel arms are fully welded for maximum stability and durability. Fully welded seat pan is through bolted to securely fasten to steel arms. Full length, one piece, pick resistant, securely fixed polyurethane arm caps protect high use top and front edges of the chair. The self-skinned polyurethane arm cap is molded over an 11 gauge steel armature and attaches with a secure steel-to-steel connection to ensure the arm cap stays connected to the frame. Injection molded nylon feet are engineered for strength and to protect floors. Made in the U.S.A.

## Performance Test Standards

- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (500 lbs from 18")

## Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Color

**Polyurethane Arm Caps:** Raven, Taupe

**Nylon Feet:** Raven, Taupe

## Options

**Seat:** Seats are offered as either short or full apron.

**Fit:** Seat and back junction is available as standard fit or with a clean out. The clean out version is available with an open bottom. The standard fit is available with an open or closed bottom. The closed bottom conceals access from the underside of the chair and has a plate between the seat and back to eliminate pass through.

**Upholstery:** Seats, backs and arms are available in different fabrics. Upholstered flammability standard upgradeable to TB133.

## Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

## Assembly

None required

## Installation

None required

## Warranty

5 year limited replacement warranty; lifetime structural warranty on internal steel frame. Refer to Norix Terms and Conditions for details.

## Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.