

Multi-Purpose Table



SPECIFICATIONS



T-Base	Dimensions	Weight	Height
MP1860	(18" x 60")	59 lbs	29"
MP2460	(24" x 60")	74 lbs	
MP3060	(30" x 60")	91 lbs	
X-Base	Dimensions	Weight	Height
MP3600	(36" Diameter)	53 lbs	29"
MP3636	(36" x 36")	63 lbs	
MP4200	(42" Diameter)	66 lbs	
MP4242	(42" x 42")	79 lbs	

*Intended for indoor use only



DETAILS

Color

Legs: Metallic Silver, Black

Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut, Titanium Evolve

T-Edge: Bark (Kensington Maple, Asian Sun, Montana Walnut), Black (Wild Cherry, Titanium Evolve)

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: 1³/₄" 12 gauge steel tubes, fully welded and sealed on exposed ends. Glides adjust for leveling, but are tamper resistant as a security precaution. Factory, powder coated for optimum scratch and corrosion resistance.

Top: 45 lb density M3 grade particle board with embedded T-nuts sandwiched with decorative laminate and backer sheet. Edge is routed to receive glued and pinned black vinyl T-molding. 1¹/₄" thick edge profile.

Made in the U.S.A.

Installation

None required

Warranty

10 year limited replacement warranty

Maintenance

Laminate Tops: For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

Base: Norix recommends the use of soap and water for both the regular cleaning maintenance and deep-scrub cleaning of powder-coated seal.

TESTING

Performance Test Standards

Product tested to 500 lb static load

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG
- Complies with Healthier Hospitals guidelines