

SPECIFICATIONS



Model

FD18

Weight

6.2 lbs

Dimensions

Mirror Diameter 18"

Frame Diameter 20"

Depth 6.75"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

24" Diameter (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 360° view.

Frame: 3/16 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

FD24

Weight

9.8 lbs

Dimensions

Mirror Diameter 24"

Frame Diameter 26"

Depth 8.5"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

18" Diameter (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 360° view.

Frame: 3/16 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

HD18

Weight

5.8 lbs

Dimensions

Length 20"

Height 10"

Depth 5.5"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

24" or 36" Mirror (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 180° view.

Frame: 3/16 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

HD24

Weight

8.1 lbs

Dimensions

Length 25.75"

Height 13"

Depth 7"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

18" or 36" Mirror (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 180° view.

Frame: 3/16 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

HD36

Weight

13.9 lbs

Dimensions

Length 37"

Height 19"

Depth 7.5"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

18" or 24" Mirror (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 180° view.

Frame: 3/16 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

MFSST-RND-1600

Weight

4.6 lbs

Dimensions

Mirror Diameter 14"

Frame Diameter 16"

Depth 1/4"

*Intended for indoor use only



DETAILS

Color

Mirror: Bright Mirror Finish

Frame: Beige

Assembly

Align mirror holes with frame holes. Attach to wall or embed plate.

Fabrication & Material

Mirror: .04" (1 mm) stainless steel with bright annealed or #8 mirror finish on one side.

Frame: 1/4 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

MFSST-REC-1620

Weight

6.8 lbs

Dimensions

Mirror	14" x 18"
Frame	16" x 20"
Depth	1/4"

*Intended for indoor use only



DETAILS

Color

Mirror: Bright Mirror Finish

Frame: Beige

Assembly

Align mirror holes with frame holes. Attach to wall or embed plate.

Fabrication & Material

Mirror: .04" (1 mm) stainless steel with bright annealed or #8 mirror finish on one side.

Frame: 1/4 x 1" steel has recessed holes for fastening to any solid flat surface. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

QD12

Weight

7.2 lbs

Dimensions

Length 19"

Height 9.5"

Depth 13.5"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

18" Mirror (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 90° view.

Frame: 3/16 x 1" steel has recessed holes for fastening and slotted flange for mirror. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

SPECIFICATIONS



Model

QD18

Weight

9.5 lbs

Dimensions

Length 27"

Height 9"

Depth 19"

*Intended for indoor use only



DETAILS

Color

Mirror: Silver

Frame: Cream

Options

12" Mirror (See separate specification sheets)

Assembly

Fit mirror and foam backing to frame. Attach to ceiling or wall.

Fabrication & Material

Mirror: 1/8" polycarbonate with a pure silver reflective coating on inside surface. Fully enclosed foam insert fills cavity to reduce flexing and enhance strength. 90° view.

Frame: 3/16 x 1" steel has recessed holes for fastening and slotted flange for mirror. Powder coated to provide durable smooth finish.

Installation

Installation required. Refer to manufacturer instructions; confirm surface material for specification of correct fittings (mounting hardware not included).

Warranty

3 year limited replacement warranty

Maintenance

When cleaning stainless steel, Norix recommends the use of a cleaner made especially for stainless steel products.

TESTING

Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.