

## SPECIFICATIONS



### Model

EE

### Weight

215 lbs

\*Intended for indoor use only

### Dimensions

Seat Height 18"

Seat Width 69"

Overall Height 32.5"

Depth 29"

Width 75"

Arm Height 26.4"

**Stinson**  
SEE / SAMPLE / SPEC



## DETAILS

### Color

Arm Caps and Feet: Raven

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

### Options

Available in California TB133 compliant upholstery

### Assembly

None required

### Fabrication & Material

Frame: The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

Cushions: Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

Arm Panel: Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

## SPECIFICATIONS



### Model

EC

### Weight

141 lbs

\*Intended for indoor use only

### Dimensions

Seat Height 18"

Seat Width 46"

Overall Height 32.5"

Depth 29"

Width 52"

Arm Height 26.4"

**Stinson**  
SEE / SAMPLE / SPEC



## DETAILS

### Color

Arm Caps and Feet: Raven

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Available in California TB133 compliant upholstery

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

### Assembly

None required

### Fabrication & Material

Frame: The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

Cushions: Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

Arm Panel: Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

## SPECIFICATIONS



### Model

EA

### Weight

100 lbs

\*Intended for indoor use only

### Dimensions

Seat Height 18"

Seat Width 23"

Overall Height 32.5"

Depth 29"

Width 29"

Arm Height 26.4"

Stinson  
SEE / SAMPLE / SPEC



## DETAILS

### Color

Arm Caps and Feet: Raven

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Available in California TB133 compliant upholstery.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade A, Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

### Assembly

None required

### Fabrication & Material

Frame: The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

Cushions: Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

Arm Panel: Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")